NAP benchmarks near the excavations of Wijnaldum-Tjitsma, Englum and Ezinge

An explanation of NAP heights, supplementing A. Nieuwhof & P.C. Vos: New data from terp excavations on sea-level index points and salt marsh sedimentation rates in the eastern part of the Dutch Wadden Sea.

Elevations measured in NAP cannot simply be compared, especially not when there is a large time span or distance between the measurements. That is clearly the case in this study which compares Wijnaldum in the western part of the province of Friesland and Englum and Groningen in the western part of the province of Groningen. These terps were excavated within a time span of 80 years. We therefore need to assess the history of the local NAP benchmarks and their relation with natural or man-induced subsidence. The latter is especially relevant in the northern-Netherlands, where the extraction of natural gas and salt have caused considerable subsidence in recent times.

The accompanying table shows the geographically differentiated histories of NAP benchmarks that were used during the excavations and of benchmarks in the vicinity of these locations. Although some benchmarks only have a short history, these data together provide an overview of adjustments of NAP benchmarks and of subsidence relative to NAP per region, over the last century. Salt extraction in northwest Friesland only started in 1996, after the excavation in Wijnaldum had ended. The table shows that adjustments before the start of salt extraction in Friesland amounted to 0.8-1.0 cm/10 years in both provinces, suggesting that gas extraction in Groningen hardly influenced NAP heights near Englum and Ezinge, if at all.

NWP = Nauwkeurigheidswaterpassing ('precision leveling'); see text.

Wijnaldum

Excavated 1991-1993.

NAP benchmark: 005D0040

Reference height: 0.5441 m +NAP (1982); 2nd NWP

Distance to excavation: 750 m.

Note: salt extraction has resulted in considerable adjustments since 1996.

Englum

Excavated 2000.

NAP benchmark: 007A0037

Reference height: 1.2871 m +NAP (1991); 2nd NWP

Distance to excavation: 250 m

Note: adjustments of this benchmark indicate gradual subsidence, of 0.8 cm/10 years since 1957.

Ezinge

Excavated 1923-1934.

NAP benchmark: 007A0035

Reference height: 0.8119 m +NAP (1921); 1st NWP

Distance to excavation: 3.8 km

Note: The brass bolt of benchmark 007A0022 was replaced by 007A0211 when the building to which it was attached

was rebuilt in 1981.

Adjustments of benchmarks near Ezinge indicate gradual subsidence, of 0.9 cm/10 years since 1957.

The histories of NAP benchr	marks near the ex	xcavations of W	ijnaldum, Englum a	nd Ezinge. D	Data provided by R	kijkswaterstaat.										
			inglum (Excavation 2000) Ezinge (Excavation 1923-1934)								1					
Wijnaldum (Excavation 1991-1 Benchmark no. 005D0015			005D0040		05G0266	007A0037		007A0022 >>>>>>>		>>>>>>	007A0211		007A0035		007A0028	
Address Hauleweg 9			Alde Leane 2		Buorren 5	Englumerweg 11		Garnwerd, Oostumerweg 8		Garnwerd, Oostumerweg 8		Garnwerd, '125 m S. of ferry'		Ezinge, Torenstraat 2		
Year	NWP 2	NWP 5	NWP 2	NWP 5	NWP 5	NWP 2	NWP 5	NWP 1	NWP 2	NWP 5	NWP 2	NWP 5	NWP 1	NWP 2	NWP 2	NWP 5
1921								1.3508					0.8119	0.7650)	
1933/1	0.9419															
1933/2	0.9432							_					_			
1942									1.2438					0.6820		
1954 1957	0.9235					1 2005			1 2656					0.7250	1.2055 1.2481	
1957	0.9235					1.3095		_	1.2656		ition Groningen 196	:2		0.7250 0.7250		
1969									1.2440	Start gas extra	1.0564			0.7169		
1972						1.3129			1.2469						1.2471	
1975						1.2998			1.2377						1.2365	İ
1976	0.9047															
1978/1			0.5253			1.3006			1.2380						1.2377	
1978/2									1.2375							
1980						4 2000	4 2062		4 2207	4 2202	4.0453	4 0247			1.2377	4 2240
1981		-				1.2968	1.2862		1.2307	1.2202	1.0452	1.0347			1.2354	1.2248
1982			0.5441													
1987	0.8921	0.8863				1.2876	1.2782			1.2129	1.0364	1.0274			1.2282	1.2190
1989 1990						1.2904 1.2863	1.2809 1.2774			1.2116 1.2221	1.0353 1.0301	1.0261 1.0215	1		1.2299 1.2260	1.2205 1.2172
1991						1.2871	1.2774			1.2221	1.0301	1.0213			1.2200	1.21/2
1992						1.2864	1.2771									
1993	0.885	0.8816				1.2864	1.2771			1.2040	1.0271	1.0185			1.2262	1.2171
1994/1						1.2868	1.2776									
1994/2	S	start salt extract	ion Friesland 1996			1.2868										İ
1996						1.2843	1.2737									
1997/1	0.8838	0.8777				1.2831	1.2736									
1997/2	0.8781	0.8761	0.5164	0.5144		1.2845	1.2738			4 4004	4 0074	0.0070			4 2240	4 2442
1998 1999	0.8791	0.8736				1.2825 1.2849	1.2727 1.2739			1.1834	1.0071	0.9979			1.2210	1.2113
2000	0.8628	0.8570	0.4787	0.4731		1.2049	1.2739									
2001	0.8542	0.8481	0.4653	0.4594	1											
2002	0.8481	0.8420	0.4505	0.4447												
2003/1	0.8355	0.8297		0.4247	0.8887	1.2697	1.2567			1.1584	0.9852	0.9729				1.1924
2003/2		0.8319														
2004		0.8266		0.4143	1											
2005		0.8206		0.4039	1											
2006		0.8218		0.4055												
2007		0.8210		0.4022			1 3630			1.1500		0.0722				1 2010
2008		0.8195		0.4000	1		1.2620			1.1593		0.9738				1.2016
2009		0.8184		0.3994	i i											
2010		0.8170		0.3960	i i											
2011		0.8162		0.3962												
2012		0.8152		0.3935			4.05.1			4 100		0.0=:=				4 4000
2013/1		0.8089		0.3867	0.8433		1.2541			1.1603		0.9748				1.1968
2013/2		0.8111														
2014	an alama and district	0.8092		0.3883	0.8431											
Adjustments in published be Start-1997		1933: -0.06 m	from 10	78: -0.01 m		from 10	957: -0.03 m		from	n 1942: -0.05 m					from 10	57: -0.03 m
	irom		11011119		 	irom 19			iron						irom 19	
1997-2013		-0.07 m		-0.13 m			-0.02 m			-0.02 m					1	-0.01 m
Total, including difference NWP 2 and 5, earliest-2013	trom	n 1933:-0.13 m	trom 19	78: -0.14 m	from 2003: -0.05 m	from 19	957: -0.05 m		tron	n 1942: -0.07 m			(perio	d too short)	trom 19.	57: -0.04 m
Average subsidence/10																
years until 1997		1 cm		0.5 cm			0.8 cm			0.9 cm						0.9 cm

Level of excavation NAP reference point

Computed heights if 007A0022 had been continuous: height of bolt 007A0211 +0.1855 m for relocation.

Rijkswaterstaat: probably not correct

Rise instead of subsidence; 1942 data not reliable.

Assumed height, allowing for 4 cm subsidence between 1957/1959 and 1921.